

# CHARLAND THERMOJET INC


Mixing units and hoses stations

16350 Blv. Gouin Ouest, Ste-Geneviève, Québec H9H 1E1

Toll free: 1-800-624-4709 Tel : 514-624-4772 Fax : 624-4776

E-mail: [info@charlandthermojet.com](mailto:info@charlandthermojet.com) Web: [www.charlandthermojet.com](http://www.charlandthermojet.com)

## CHARLAND THERMOJET HOSES FOR CLEANING TASK WITH VERY HOT WATER



### 1580 SERIES

I. D. (po.)	O. D. (po.)	Tube (po.)	Ply	Cover (po.)	W. P. (PSI)	WT. (lb/pi)
1/2	0.96	3.32	2	1/16	150	0.34
5/8	1.13	3.32	2	3/32	150	0.46
3/4	1.26	3.32	2	3/32	150	0.52
1	1.55	1/8	2	3/32	150	0.72
1-1/4	1.80	1/8	2	3/32	150	0.87
1-1/2	2.10	1/8	2	1/8	150	1.11

**Tube** : White FDA SBR

**Reinforcement** : Fabric reinforced 2 ply

**Cover** : White or black FDA SRB abrasion resistant rubber.

**Maximum temperature** : 93 °C (200 °F)

### Available colors:

- White
- Blue
- Black
- Red
- Gray

# CHARLAND THERMOJET INC

Mixing units and hoses stations

16350 Blv. Gouin Ouest, Ste-Geneviève, Québec H9H 1E1

Toll free: 1-800-624-4709 Tel : 514-624-4772 Fax : 624-4776

E-mail: [info@charlandthermojet.com](mailto:info@charlandthermojet.com) Web: [www.charlandthermojet.com](http://www.charlandthermojet.com)

## INDUSTRIAL HOSES FOR GENERAL PURPOSE

High quality industrial hoses for general applications. Perfect for transporting air or liquids depending on the needs. Available in several size.



<b>Applications :</b>	General purpose for air or water line inside or outside.				
<b>Cover :</b>	Red smooth weather and abrasion resistant PVC				
<b>Reinforcement :</b>	Multiple layers of synthetic yarns				
<b>Tube :</b>	Black oil resistant PVC blend				
<b>Temperature :</b>	- 30 °C to 70 °C (-22 °F to 160 °F).				
<b>Nominal I. D.</b>	<b>Nominal O. D.</b>	<b>PSI</b>	<b>WT. (lbs)</b>	<b>Standard pkg.</b>	<b>Part number</b>
1/4"	0.55"	250	0.13	300'	GP-025-250
3/8"	0.67"	200	0.19	300'	GP-038-200
3/8"	0.71"	250	0.19	300'	GP-038-250
1/2"	0.83"	200	0.23	300'	GP-050-200
1/2"	0.87"	250	0.27	300'	GP-050-250
3/4"	1.16"	250	0.42	300'	GP-075-250
1"	1.42"	200	0.54	300'	GP-100-200
1-1/4"	1.73"	150	0.64	100'	GP-125-150
1-1/2"	2.05"	150	0.74	100'	GP-150-150
2"	2.60"	150	1.01	100'	GP-200-150
<b>Cut lengths :</b>	Plus 5%				
<b>Standard lengths :</b>	1/4" – 1" 50' / 100' / 300'. 1-1/4" – 2" 50' / 100'.				
<b>Recommended couplings</b>	High pressure 1/2"-1" for air service if working pressure exceeds 150 PSI. High pressure, short shank, universal, or combination nipples for all other sizes, or if used in water service.				

For more information or any questions please contact us or view our complete catalog.

# CHARLAND THERMOJET INC

Mixing units and hoses stations

16350 Blv. Gouin Ouest, Ste-Geneviève, Québec H9H 1E1

Toll free: 1-800-624-4709 Tel : 514-624-4772 Fax : 624-4776

E-mail: [info@charlandthermojet.com](mailto:info@charlandthermojet.com) Web: [www.charlandthermojet.com](http://www.charlandthermojet.com)

**Cover** : Red\*\* smooth weather and abrasion resistant PVC.

**Reinforcement** : Multiple layers of synthetic yarns.

**Tube** : Black oil resistant PVC blend.

**Applications** : Air, water, oils, dilute chemical, agricultural spray solutions, insecticides, animal fats

**Temperature range** : -25 °C to 65 °C (-15 °F to 150 °F).

I. D. (po.)	O. D. (po.)	W. P. (PSI)	WT. (lb/100')	Part number
1/4	0.50	300	8	POLYA-025-**
5/16	0.63	300	13	POLYA-031-**
3/8	0.63	300	11	POLYA-038-**
1/2	0.81	300	18	POLYA-050-**
5/8	0.91	250	19	POLYA-063-**
3/4	1.13	250	30	POLYA-075-**
1	1.41	250	41	POLYA-100-**

**Standard lengths** : 1/4" – 1/2"- 500' reels, 5/8"-1"-300' reels.

\*\* Specify colour required : **R**(red), **Y**(yellow), **BL**(blue), **G**(gray).

\* Working pressure is measured at 20 °C (68 °F), reduce pressure by 50% at maximum working temperature 65 °C (150 °F).

**Recommended couplings** : High pressure 1/2"-1" for air service if working pressure exceeds 150 PSI. High pressure, short shank, universal, or combination nipples for all other sizes, or if used in water service.

## LOW TEMPERATURE TUNDRA PVC AIR HOSE

**Cover** : Yellow super abrasion resistant PVC / polyurethane.

**Reinforcement** : Multiple layers of synthetic yarn.

**Tube** : Heat, oil and chemical resistant PVC / polyurethane.

**Applications** : Where extreme flex resistance at low and high temperature is required.

Temperature : -40 °C to 85 °C (-40 °F to 185 °F).

I. D. (po.)	O. D. (po.)	Pressure (PSI)	WT. (lb/100')	Part number
1/4	0.500	300	7.4	TUNDRA-025
3/8	0.625	300	13.4	TUNDRA-038

**Standard lengths** : 500' reel.

**Cut lengths** : plus 5%.

**Recommended couplings** : Brass barbed attached with crimped on ferrules.